

# PST-6/E/PA

# PST-6/E/PB

- Piastra di deviazione per elettrovalvole luce 6 (CETOP 3) con collegamento P in A e B in T.
  - Pressione massima 350 Bar.
  - Peso Kg. 0,35.
- Diversion plate for solenoid valves port 6 (CETOP 3), with connection of P to and B to T.
  - Max. pressure 350 Bar.
  - Weight .35 Kgs.
- Plaque de déviation pour électrovalves ouverture 6 (CETOP 3), avec connexion P en A et B en T.
  - Pression max. 350 Bar.
  - Poids 0,35 Kg.
- Ablenkungsplatte für Elektroventile Lichtweite 6 (CETOP 3), mit Verbindung von P zu A und B zu T.
  - Maximaldruck 350 Bar.
  - Gewicht 0,35 Kg.

- Piastra di deviazione per elettrovalvole luce 6 (CETOP 3) con collegamento P in B e A in T.
  - Pressione massima 350 Bar.
  - Peso Kg. 0,35.
- Diversion plate for solenoid valves port 6 (CETOP 3), with connection of P to B and A to T.
  - Max. pressure 350 Bar.
  - Weight .35 Kgs.
- Plaque de déviation pour électrovalves ouverture 6 (CETOP 3), avec connexion P en B et A en T.
  - Pression max. 350 Bar.
  - Poids 0,35 Kg.
- Ablenkungsplatte für Elektroventile Lichtweite 6 (CETOP 3), mit Verbindung von P zu B und A zu T.
  - Maximaldruck 350 Bar.
  - Gewicht 0,35 Kg.

