



This cavity plug blocks all ports.

TECHNICAL DATA

NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

| | |
|----------------------------|-------------------------|
| Cavity | T-18A |
| Series | 4 |
| Maximum Operating Pressure | 350 bar |
| Port Configuration | 2 Port |
| Valve Hex Size | 41,3 mm |
| Valve Installation Torque | 474 - 508 Nm |
| Seal kit - Cartridge | Buna: 990018007 |
| Seal kit - Cartridge | EPDM: 990018014 |
| Seal kit - Cartridge | Polyurethane: 990018002 |
| Seal kit - Cartridge | Viton: 990018006 |
| Model Weight | 1.44 kg. |

CONFIGURATION OPTIONS

Model Code Example: XKCAXXN

| CONTROL | (X) ADJUSTMENT RANGE | (X) SEAL MATERIAL | (N) MATERIAL/COATING |
|----------------|-----------------------------|-------------------------------|---|
| X - | X - | N Buna-N E EPDM V Viton | Standard Material/Coating /AP Stainless Steel, Passivated /LH Mild Steel, Zinc-Nickel |

TECHNICAL FEATURES

- Cartridges configured with EPDM seals are for use in systems with phosphate ester fluids. Exposure to petroleum based fluids, greases and lubricants will damage the seals.
- Corrosion resistant cavity plugs are intended for use in corrosive environments and are identified by the model code suffix /AP (see CONFIGURATION section). The bodies of these plugs are made from high strength lean duplex stainless steel. Internal parts are made from carbon steel leaded alloy, the same as standard plugs.